MERLO

P 40.17 US STABILIZERS

- MAXIMUM LOAD CAPACITY: 10,000 LBS
- MAXIMUM LIFT HEIGHT: 54’ 8”
- MAXIMUM REACH: 41’ 0”
- LOAD CAPACITY AT MAXIMUM LIFT HEIGHT: 5,500 LBS
- LOAD CAPACITY AT MAXIMUM FORWARD REACH: 1,100 LBS

AMS-Merlo.com 1205 Galleria Blvd., Rock Hill, SC 29730 803-327-4949

SPECIFICATIONS:
P 40.17 US STABILIZERS

Power / 4 Cylinder Turbo Diesel	Deutz/101 HP
Transmission	2 Speed / Hydrostatic
Maximum Speed	25 MPH
Total Unladen Mass	22,320 LBS
Boom Sideshift (Inches)	Standard / 17
Frame Leveling	Standard / ±10%
Load Sensing Hydraulic Pump (PSI-gal/min)	3,045-38
Fuel Capacity	40 Gallons
Hydraulic Oil Capacity	37 Gallons
Tires	405/70-24
4 Wheel Drive / 3 Steering Modes	Standard
Hydraulic System	Load-sensing
Control and Command Center	Electronic MERlin
Independent Front Stabilizers	Standard

Dimensions							
A	19’ -0”	D	4’-3”	H	7’-9”	R	13’-3”
B	4’-9”	E	15’-7”	M	3’-3”		
C	9’-4”	F	1’-6”	P	8’-2”		

The technical data and other information in this document are not binding. We reserve the right to modify our products without prior notice as part of our policy of continuous technical improvement.

DEALER INFORMATION: